

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name POINT PU 301 METAL & WOOD FIX
Pure substance/mixture Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known.

1.3 Details of the supplier of the safety data sheet

Company Name
UAB „TEGRA STATE”
Kirtimų g. 67
LT-02244 Vilnius
Tel./faksas +370 5 266 11 67
www.tegra.lt, www.tegrastate.lt
E-mail address info@tegra.lt

1.4 Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Regulation (EC) No 1272/2008 Not classified

2.2 Label Elements

Not classified
Signal word None
Hazard statements Not classified

EU Specific Hazard Statements

EUH208 - Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction
EUH210 - Safety data sheet available on request
EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust
EUH204 - Contains isocyanates. May produce an allergic reaction

2.3 Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight – %	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Xylene (reaction mass of ethylbenzene and xylene)	905-588-0	RR-45541-4	5 - <10	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)	STOT RE 2 (H373): C>=10%	01-2119488216-32-xxxx
Titanium dioxide	236-675-5	13463-67-7	1 - <5	Carc. 2 (H351i)		01-2119489379-17-XXXX
Aromatic Polyisocyanate	–	53317-61-6	0.1 - <1	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)		[7]
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	0.01 - <0.1	Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119491304-40-XXXX
4,4'-Methylenediphenyl diisocyanate	202-966-0	101-68-8	0.01 - <0.1	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	01-2119457014-47-XXXX

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

Cheminis pavadinimas	EC No	CAS Nr	Svoris – %	Klasifikavimas pagal reglamentą (EB) Nr. 1272/2008 (CLP)	Konkreči koncentracijos riba (SCL):	REACH registracijos numeris
Toluene diisocyanate	247-722-4	26471-62-5	0.01 - <0.05	Acute Tox. 1 (H330) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) Aquatic Chronic 3 (H412)	Resp. Sens. 1 :: C ₂ ≥ 0.1%	01-2119454791-34-XXXX

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	Prolonged contact may cause redness and irritation.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.

5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of toxic and corrosive gases/vapours.
Hazardous combustion products	Carbon monoxide. Carbon dioxide (CO ₂). Hydrocarbons. Nitrogen oxides (NO _x). Aldehydes. Hydrochloric acid. Sulphur oxides.

5.3 Advice for firefighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.
Other information	Ventilate the area. Prevent further leakage or spillage if safe to do so.
For emergency responders	Use personal protection recommended in Section 8.

6.2 Environmental precautions

Environmental precautions	Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
----------------------------------	--

6.3 Methods and material for containment and cleaning up

Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.

6.4 Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
------------------------------------	--

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture.

7.3 Specific end use(s)

Specific Use(s) Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ S*

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)			
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	221 mg/m ³	
worker Long term Local health effects	Inhalation	221 mg/m ³	
worker Short term Local health effects	Inhalation	442 mg/m ³	
worker Long term Systemic health effects	Dermal	212 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)			
4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	50 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	0.1 mg/m ³	
worker Short term Local health effects	Dermal	28700 µg/cm ²	
worker Short term Local health effects	Inhalation	0.1 mg/m ³	
worker Long term Systemic health effects	Inhalation	0.05 mg/m ³	
worker Long term Local health effects	Inhalation	0.05 mg/m ³	

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

Toluene diisocyanate (26471-62-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	0.035 mg/m ³	
worker Short term Systemic health effects	Inhalation	0.14 mg/m ³	
worker Long term Local health effects	Inhalation	0.035 mg/m ³	
worker Short term Local health effects	Inhalation	0.14 mg/m ³	

Derived No Effect Level (DNEL)			
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	65.3 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	260 mg/m ³	
Consumer Long term Local health effects	Inhalation	65.3 mg/m ³	
Consumer Short term Local health effects	Inhalation	260 mg/m ³	
Consumer Long term Systemic health effects	Dermal	125 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	12.5 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	25 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	0.05 mg/m ³	
Consumer Short term Systemic health effects	Oral	20 mg/kg bw/d	
Consumer Short term Local health effects	Dermal	17200 µg/cm ²	
Consumer Short term Local health effects	Inhalation	0.05 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	0.025 mg/m ³	
Consumer Long term Local health effects	Inhalation	0.025 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.327 mg/l
Marine water	0.327 mg/l
Microorganisms in sewage treatment	6.58 mg/l
Freshwater sediment	12.46 mg/kg dry weight
Soil	2.31 mg/kg dry weight

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

4,4'-Methylenediphenyl diisocyanate (101-68-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Soil	1 mg/kg dry weight
Sewage treatment plant	1 mg/l
Freshwater - intermittent	10 mg/l

Toluene diisocyanate (26471-62-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.013 mg/l
Marine water	0.00125 mg/l
Microorganisms in sewage treatment	>1 mg/l
Soil	>1 mg/kg dry weight

8.2 Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment:

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

Hand protection

Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374

Skin and body protection

Suitable protective clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Rekomenduojamas filtro tipas:

Organinės dujos ir garų filtras, atitinkantis EN 14387 reikalavimus. AX.

Recommended filter type:

Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls No information available.

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	White
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	Not applicable .	
Melting point / freezing point	No data available	
Boiling point / boiling range	Not applicable . °C	
Flash point	> 61 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	600000 mm ² /s	
Dynamic viscosity	600000 mPa s	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2 Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	1.23 g/cm ³

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 10: Stability and reactivity

10.1 Reactivity	
Reactivity	No information available.
10.2 Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical impact	None
Sensitivity to static discharge	None
10.3 Possibility of hazardous reactions	
Possibility of hazardous reactions	None under normal processing.
10.4 Conditions to avoid	
Conditions to avoid Protect from moisture.	Product cures with moisture.
10.5 Incompatible materials	
Incompatible materials	None known based on information supplied.
10.6 Hazardous decomposition products	
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects	
Information on likely routes of exposure	
Product Information	
Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Specific test data for the substance or mixture is not available. Causes mild skin irritation.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical, chemical and toxicological characteristics	
Simptomai	Nežinoma.
Numerical measures of toxicity	
Acute toxicity	
The following values are calculated based on chapter 3.1 of the GHS document	
ATEmix (dermal)	13,894.90 mg/kg
ATEmix (inhalation-vapour)	70.88 mg/l

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	=3500 mg/kg (Rattus)	>10000 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
Aromatic Polyisocyanate 53317-61-6	LD50 >2000 mg/Kg (Rattus)		LC50 >3.820 mg/L (Rattus) 4h dust/mist
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-pi peridyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4- piperi dyl sebacate 1065336-91-5	LD50 = 3230 mg/Kg (Rat)	LD50 >3170 mg/Kg (Rat)	
4,4'-Methylenediphenyl diisocyanate 101-68-8	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	=1.5 mg/L (Rattus) 4 h
Toluene diisocyanate 26471-62-5	=3060 mg/kg (Rattus)	= 10000 mg/kg (Oryctolagus cuniculus)	=0.107 mg/L (Rattus) 4 h (Vapour)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. May cause skin irritation.

Component Information					
Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion					Non-irritant

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Component Information					
4,4'-Methylenediphenyl diisocyanate (101-68-8)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye	0.1 mL	24 hours	Non-irritant

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Component Information			
Titanium dioxide (13463-67-7)			
4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Method	Species	Exposure route	Results
OECD GD 39	Rat	Inhalation	Sensitizing

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

Toluene diisocyanate (26471-62-5)			
Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	sensitising

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2
4,4'-Methylenediphenyl diisocyanate 101-68-8	Carc. 2
Toluene diisocyanate 26471-62-5	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information		
Titanium dioxide (13463-67-7)		
Method	Species	Results
Oral	Rat	Not Carcinogenic
Inhalation Xu et al (2010), carcinogenic activity of nanoscale TiO ₂ administered by an intrapulmonary spraying (IPS) - initiation-promotion protocol in rat lung	Rat	Carcinogenic

4,4'-Methylenediphenyl diisocyanate (101-68-8)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Limited evidence of a carcinogenic effect

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 12: Ecological information

12.1 Toxicity Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	EC50 (72hr) 2.2 mg/l (Selenastrum capricornutum)	LC50(96h) 2.6 mg/l (Oncorhynchus mykiss-OECD 203)	EC50 = 0.0084 mg/L 24 h	LC50(24h) 1 mg/l (Daphnia magna-OECD 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	–	–	–		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	–	LC50 (96h) = 0.9 mg/L	–	–		
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l (Danio rerio)	–	EC50 (24H) >1000 mg/L Daphnia magna		

12.2 Persistence and degradability Persistence and degradability

No information available.

Component Information			
Aromatic Polyisocyanate (53317-61-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)		biodegradation	34 % Not readily biodegradable

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

12.3 Bioaccumulative potential

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	3.15	25.9
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51	200
Toluene diisocyanate 26471-62-5	–	5

12.4 Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	The substance is not PBT / vPvB
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	The substance is not PBT / vPvB
4,4'-Methylenediphenyl diisocyanate 101-68-8	The substance is not PBT / vPvB
Toluene diisocyanate 26471-62-5	The substance is not PBT / vPvB

12.6 Other adverse effects

Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste from residues/ unused products

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging

Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information

Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work.

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59).

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV).

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	RG 4bis, RG 84
4,4'-Methylenediphenyl diisocyanate 101-68-8	RG 62
Toluene diisocyanate 26471-62-5	RG 62

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	Development (Category 2)

Denmark

Norway

15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa.

No

Chemical Safety Assessment has been carried out for this mixture

SAFETY DATA SHEET

according to (EC) No. 1907/2006 and (EC) No. 1272/2008



Printing date 02.06.2020

Revision: 17.12.2020

TRADE NAME: POINT PU 301 METAL & WOOD FIX

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product	Safety & Regulatory Affairs
Revision date	17-Dec-2020

Indication of changes

Revision note	Not applicable.
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.