

## SECTION 1: Identification of the substance/mixture and of the company/undertaking




- **1.1 Product identifier**
- **Trade name:** FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** One-component polyurethane foam - gun grade
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
UAB „TEGRA STATE“  
Kirtimų g. 67, LT-02244 Vilnius  
Tel./faksas +370 5 266 11 67  
www.tegra.lt, www.tegrastate.lt
- **Further information obtainable from:**  
e-mail: info@tegra.lt
- **1.4 Emergency telephone number:** In case of emergency, consult physician

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

|               |           |  |
|---------------|-----------|--|
| Aerosol 1     | H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated.   |
| Acute Tox. 4  | H332      | Harmful if inhaled.  |
| Skin Irrit. 2 | H315      | Causes skin irritation.  |
| Eye Irrit. 2  | H319      | Causes serious eye irritation.   |
| Resp. Sens. 1 | H334      | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin Sens. 1  | H317      | May cause an allergic skin reaction.                                       |
| Carc. 2       | H351      | Suspected of causing cancer.   |
| STOT SE 3     | H335      | May cause respiratory irritation.  |
| STOT RE 2     | H373      | May cause damage to organs through prolonged or repeated exposure.         |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02
GHS07
GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
diphenylmethanediisocyanate, isomeres and homologues
- **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.

(Contd. on page 2)

**Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM**

(Contd. of page 1)

- H319 Causes serious eye irritation.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H317 May cause an allergic skin reaction.  
 H351 Suspected of causing cancer.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

- P102 Keep out of reach of children.  
 P201 Obtain special instructions before use.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection.  
 P284 In case of inadequate ventilation wear respiratory protection (a protective mask with an appropriate gas filter - i.e. type A1 according to standard EN 14387).  
 P302+P352 IF ON SKIN: Wash with plenty of water/soap.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of container to in accordance with local/regional/national/ international regulation.

**Additional information:**

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.  
 Contains isocyanates. May produce an allergic reaction.

**SECTION 3: Composition/information on ingredients**
**3.2 Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

|   |  |        |
|---|--|--------|
| CAS: 9016-87-9  | diphenylmethanediisocyanate, isomers and homologues<br>⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;<br>⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;<br>Skin Sens. 1, H317; STOT SE 3, H335 | 35-40% |
| CAS: 115-10-6<br>EINECS: 204-065-8<br>Reg.nr.: 01-2119472128-37 | dimethyl ether<br>⚠ Flam. Gas 1, H220; Press. Gas C, H280  | 8-12%  |
| CAS: 13674-84-5<br>Reg.nr.: 01-2119447716-31                    | tris(2-chlorisopropyl)-phosphate<br>⚠ Acute Tox. 4, H302   | 12-16% |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 01-2119486557-22  | propane<br>⚠ Flam. Gas 1, H220; Press. Gas C, H280   | 1-5%   |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Reg.nr.: 01-2119486557-22  | isobutane<br>⚠ Flam. Gas 1, H220; Press. Gas C, H280   | 1-5%   |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

**Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM**

(Contd. of page 2)

### **SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Foam  
CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)  
Hydrogen cyanide (HCN)
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources.  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Do not flush with water or aqueous cleansing agents  
Ensure adequate ventilation.

(Contd. on page 4)

**Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM**

(Contd. of page 3)

## 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Ensure that suitable extractors are available on processing machines
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.

### Information about fire - and explosion protection:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

- Observe official regulations on storing packagings with pressurised containers.

#### Information about storage in one common storage facility:

- Do not store together with acids.
- Do not store together with alkalis (caustic solutions).
- Store away from oxidising agents.

#### Further information about storage conditions:

- Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- Protect from humidity and water.
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:** No further data; see item 7.

### 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

|     |   |
|-----|---|
| WEL | Short-term value: 0.07 mg/m <sup>3</sup><br>Long-term value: 0.02 mg/m <sup>3</sup><br>Sen; as -NCO |
|-----|---|

**CAS: 115-10-6 dimethyl ether**

|     |   |
|-----|---|
| WEL | Short-term value: 958 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 766 mg/m <sup>3</sup> , 400 ppm |
|-----|---|

- Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

(Contd. on page 5)

## Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM

(Contd. of page 4)

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### · Protection of hands:



Protective gloves

Protective gloves according to EN 374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye protection:



Tightly sealed goggles

Wear airtight protective goggles EN 166

### · Body protection: Protective work clothing EN 13688

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

|         |                                    |
|---------|------------------------------------|
| Form:   | Aerosol                            |
| Colour: | According to product specification |
| Odour:  | Characteristic                     |

#### · Change in condition

|  |               |
|--|---------------|
| Melting point/freezing point:            | Undetermined. |
| Initial boiling point and boiling range: | Undetermined. |

|              |                             |
|--------------|-----------------------------|
| Flash point: | Not applicable, as aerosol. |
|--------------|-----------------------------|

|                       |        |
|-----------------------|--------|
| Ignition temperature: | 199 °C |
|-----------------------|--------|

|                            |                              |
|----------------------------|------------------------------|
| Auto-ignition temperature: | Product is not selfigniting. |
|----------------------------|------------------------------|

|                       |                                 |
|-----------------------|---------------------------------|
| Explosive properties: | Heating may cause an explosion. |
|-----------------------|---------------------------------|

#### · Explosion limits:

|        |            |
|--------|------------|
| Lower: | 3.0 Vol %  |
| Upper: | 18.6 Vol % |

|          |                 |
|----------|-----------------|
| Density: | Not determined. |
|----------|-----------------|

(Contd. on page 6)

**Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM**

(Contd. of page 5)

- |  |  |
|--|--|
| · <b>Solubility in / Miscibility with water:</b> | Insoluble.                                 |
| · <b>Solvent content:</b><br>VOC (EC)            | 17.2 %                                     |
| · <b>9.2 Other information</b>                   | No further relevant information available. |

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Contact with water releases flammable gases.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Hydrogen cyanide (prussic acid)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**  
Harmful if inhaled.
- **LD/LC50 values relevant for classification:**
- CAS: 115-10-6 dimethyl ether**
- Inhalative LC50/4 h 308 mg/l (rat)
- CAS: 13674-84-5 tris(2-chlorisopropyl)-phosphate**
- Oral LD50 3,600 mg/kg (rat)
- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**  
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)

**Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM**

(Contd. of page 6)

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
  - **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
  - **European waste catalogue**
- |           |   |
|-----------|---|
| 08 05 01* | waste isocyanates   |
| 16 05 04* | gases in pressure containers (including halons) containing dangerous substances |
| 15 01 10* | packaging containing residues of or contaminated by dangerous substances        |
- **Uncleaned packaging:**
  - **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** 1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** 2 5F Gases.
- **Label** 2.1
- **IMDG, IATA**
- **Class** 2.1
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Gases.

(Contd. on page 8)



**Trade name: FOME FLEX 60 SECONDS FAST FIX ADHESIVE FOAM**

(Contd. of page 7)

|  |                       |
|--|-----------------------|
| · <b>EMS Number:</b>                       | F-D,S-U               |
| · <b>Transport/Additional information:</b> |                       |
| · <b>ADR</b>                               |                       |
| · <b>Limited quantities (LQ)</b>           | 1l                    |
| · <b>UN "Model Regulation":</b>            | UN1950, AEROSOLS, 2.1 |

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

### · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

### · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2