

Spray Paint, 400 ml

Designed for the decorative spray coating of various surfaces.

Supplier:

JSC "Tegra state"
Kirtimu g. 67, LT - 02244, Vilnius
Tel.: +370 5 266 1167
Fax.: +370 5 266 1167
e-mail: info@tegra.lt

Characteristics

- Fast drying
- RAL colours
- High gloss or Matte
- Good coverage (depending on the colour)
- Hard and flexible coating
- Resistant to weather conditions
- Lead- and chromate-free
- No ozone-depleting substances

Physical and chemical properties

Base type	acrylic
Colours	as per the RAL colour chart
Propellant	propane-butane mixture
Volatile Organic Compounds (VOC)	VOCs below 680 g/L
Drying time at 20°C *)	max. 15 min (dry to the touch)
Subsequent layers	up to 20 min or after 24h
Theoretical spread rate **)	approx. 2 m ² per container
Recommended coat thickness after drying	approx. 25 µm (single layer)
Recommended number of layers	2-4
*) Drying time depends on the thickness of the applied paint layer, temperature and ventilation conditions	
**) Theoretical spread rate related to the application of the enamel onto flat, nonporous groundwork in still air conditions at 20 °C, without technological losses, with coat thickness up to 25 µm. Practical spread rate may differ from the theoretical value depending on the usage conditions	

Application

The painted surface should be well-prepared by removing dust and grease.
Ambient temperature while painting: at least 18°C. Substrate should be preserved with an acrylic primer paint.
Spraying: shake the container vigorously for about 1 minute to achieve homogeneous consistency. Perform a test spray on a concealed spot. Apply the paint at a distance of 25 – 30 cm from the painted surface.
Apply subsequent layers until the desired coverage is achieved.
After applying the paint, clean the nozzle by turning the container upside down and pressing the button for a few seconds.

HAZARDS

Extremely flammable aerosol. Pressurised container: may explode if heated. Irritating to the skin. Irritating to the eyes. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Provide efficient ventilation in the workplace, use protective gloves and goggles.

Specific conditions for the safe storage and use of an aerosol product

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not burn. Do not spray on an open flame or other ignition source. Do not pierce or burn, even when emptied. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to a separate waste bin.

Read information on the label. For professional applications read the Safety Data Sheet available on upon request from info@tegra.lt

Note:

Although the information in this sheet is provided in good faith based on our knowledge and experience, it should be verified in actual use conditions. This information does not constitute a basis for any warranty claims or possible damage resulting from the misuse of the product, nor does it exempt the user from the obligation to familiarise him-/herself with and observe all legal provisions related to the use of the product.
Date of issue: 17.08.2017. (v.1)