# **TECHNICAL DATA SHEET**





# Inral GROUND ANTI-CORROSION spray paint

Protective anti-corrosion spray coating for steel, cast iron and other surfaces. Excellent adhesion to the substrate, weatherproof. The matt coating improves adhesion to surface paints and enamels. Recommended as a primer for INRAL UNIVERSAL decorative enamels or other paints. For new installations, industrial structures, electrical poles, street lamps, fences and barriers, tanks and containers, steel products, etc. For construction and damage repair, renovation and remediation on all of the above.

#### Area of use:

For new installations, industrial structures, electrical poles, street lamps, fences and barriers, tanks and containers, steel products, etc. For construction and damage repair, renovation and remediation on all of the above.

#### **Advantages:**

- · Fast drying, matt appearance
- Excellent covering and adhesion to the substrate
- · Resistant to weather conditions and water
- Resistant to temperatures up to 110°C
- · Provides excellent adhesion of the enamel topcoats
- Does not contain lead or chromate compounds
- Does not include substances that affect the ozone layer

#### **Spray passes:**

2-3 cross layer, spraying distance: 30 cm.

# **Drying times:**

- Touch dry: about 10 min.
- Other layers: 1 hour or longer without limitations

#### Yield:

1,5 m<sup>2</sup> (from one 400 ml. can, one layer).

#### **Usage:**

Clean and degrease the surface. Shake the can vigorously for 1 min. Spray evenly on the surface at a distance of 30 cm. Most effective when applied as a thin coat, with breaks, in several layers. Top coat after 1 hour or later. When finished, turn the can upside down and clean the pulveriser by holding it down for a few seconds.

**Base:** modified alkyd

Package: 400 ml



# **TECHNICAL DATA SHEET**



	-			
<b>\</b> 2t	OTV.	Mat:	ch	O O T
Jai	CLV	data	1 311	

presented separately.

# **Protection measures:**

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

# **Storage:**

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

## **Shelf life:**

10 years if appropriate storage provided.

## **Color tones:**

Art. nr.	Color	Gloss level
26-7-2-003	Grey	Matte

