TECHNICAL DATA SHEET



Inral Aerosol decor paint HAMMER EFFECT

Hammer paint is high-quality, weather-resistant, producing the impressive texture of a chisel hammer. Surfaces to be painted: metal, plastic, polystyrene, stone, clay, ceramics, glass, etc. Commonly used for painting tool boxes, mailboxes, fences, pots, etc.

INRAL

Area of use:

metal, plastic, polystyrene, stone, clay, ceramics, glass, etc. Commonly used for painting tool boxes, mailboxes, fences, pots, etc.

Advantages:

- Nostalgic hammer finish effects
- "Hammered" surface structure
- High coverage and fast drying
- Very good running properties and easy to process
- Very economic
- Weatherproof, for indoors and outdoors
- Ideal for letterboxes, stair railings, tool boxes etc.

Spray passes:

2-3 cross layer, spraying distance: 15-25 cm.

Drying times:

- Touch dry: about 20 min.
- Other layers: after 60 min.
- Dry-hard: after 12 hours

Yield:

1,5 m² (from one 400 ml. can, one layer).

Usage:

The painted surface must be clean, dry and grease-free. Shake the can vigorously for about 2 minutes. Spraying distance 15-25 cm. Test the paint in an inconspicuous place to check compatibility and colour tone. For best results, 2-3 coats are recommended. The paint dries after 24 hours. For outdoor applications, it is recommended to use on INRAL GROUND or INRAL PLASTIC PRIMER. After use, turn the can upside down and spray the valve until empty

Base: nitro resins

Package: 400 ml



UAB "TEGRA STATE", Savanorių pr. 178A, LT-03154 Vilnius, tel. +370 5 266 11 67, www.tegrastate.lt

TECHNICAL DATA SHEET



Safety data sheet:

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

Storage:

Store upright in a dry place at +5°C to +25°C. Do not expose the cans to direct sunlight or heat above 50°C.

INRAL

Shelf life:

5 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-8-1-004	Anthracite	Glossy

