TECHNICAL DATA SHEET



GRANITE EFFECT PAINT

Spray paint with granite effect. Decorative paint to create solid and real stone imitation. Sprayed on surfaces not normally made of stone, such as metal, wood, plastic, clay, ceramic, glass, etc. to give an imitation of a stone surface. For indoor or outdoor applications (protect from rain and moisture).

INRAL

Area of use:

for surfaces such as metal, wood, plastic, clay, ceramic, glass, etc.

Advantages:

- Realistic stone look
- Special rough coating
- Good coverage
- For indoor and outdoor use (protect from rain and moisture)
- Easy to use and apply
- · Ideal for DIY enthusiasts and craftsmen

Spray passes:

1-2 cross layers, spraying distance: 30 cm.

Drying times:

- Touch dry: in around 120 min.
- Complete dryness: in around 24 h.

Yield:

1,2 m² (from one 400 ml. can, one layer).

Usage:

The surface must be clean, dry and grease-free. Shake the can vigorously for 1 minute. Spraying distance 30 cm. Test the paint in an inconspicuous place to check compatibility and colour tone. For best results, use INRAL GROUND (matching the colour of the effect paint) or PLASTIC PRIMER (for plastic surfaces). Then apply GRANITE paint in 1-2 coats (with a 10-15 min break). For long-lasting use, apply INRAL LACQUER acrylic varnish on top (after 3 hours). The paint dries completely after 24 hours. After use, turn the can upside down and spray the valve until empty (about 3 sec.).

Base: alkyd resins

Package: 400 ml



UAB "TEGRA STATE", Savanorių pr. 178A, LT-03154 Vilnius, tel. +370 5 266 11 67, www.tegrastate.lt

TECHNICAL DATA SHEET

Safety data sheet:

presented separately.

Protection measures:

wear personal protection equipment (gloves / goggles). For more information, see safety data sheet.

INRAL

Storage:

store verticaly at +10 °C...+25 °C temperature and relative air humidity of max. 60%.

Shelf life:

10 years if appropriate storage provided.

Color tones:

Art. nr.	Color	Gloss level
26-8-2-001	Obsidian black	Matte
26-8-2-002	Cream	Matte
26-8-2-003	Red brick	Matte

