

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: P Plus Mega Pistol Foam 65L

1.2 Relevant identified uses of the substance or mixture and uses advised against

Assembly foam

Application of the substance / the mixture Construction chemicals

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

UAB TEGRA STATE

Savanoriu ave. 178A, LT-03154 Vilnius

Tel.+370 5 266 11 67

info@tegra.lt

www.tegrastate.lt

1.4 Emergency telephone number: European emergency number: 112 (24h)

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2

H351

Suspected of causing cancer.

STOT RE 2

H373

May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4

H332

Harmful if inhaled.

Skin Irrit. 2

H315

Causes skin irritation.

Eye Irrit. 2

H319

Causes serious eye irritation.

Skin Sens. 1

H317

May cause an allergic skin reaction.

STOT SE 3

H335

May cause respiratory irritation.

Lact.

H362

May cause harm to breast-fed children.

Aquatic Chronic 4

H413

May cause long lasting harmful effects to aquatic life.

Additional information:

Classification of the preparation with attributed H413 phrase, taking into account the content C14-C17 chlorinated alkanes, was made on the basis of acute toxicology tests; FEICA Position Paper 17.03.2014.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

GHS07

GHS08

Signal word Danger

Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomers and homologues

chlorinated paraffins, C14-17

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe gas.

P263 Avoid contact during pregnancy and while nursing.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information at: www.feica.eu/PUinfo

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:	
CAS: 85535-85-9	chlorinated paraffins, C14-17

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

vPvB:	
CAS: 85535-85-9	chlorinated paraffins, C14-17

Determination of endocrine-disrupting properties		
CAS: 1244733-77-4	tris(2-chlorisopropyl)-phosphate	List II

* SECTION 3: Composition/information on ingredients

3.1 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	30 - 60%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chlorisopropyl)-phosphate ⚠ Acute Tox. 4, H302	< 25%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33-xxxx	chlorinated paraffins, C14-17 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10); Lact., H362, EUH066 PBT; vPvB	< 20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%

SVHC	
CAS: 85535-85-9	chlorinated paraffins, C14-17

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin sur-

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

face using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Carbon dioxide.

Fire-extinguishing powder.

Foam.

Water spray.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet.

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective clothing.

Do not inhale vapour/spray.

Ensure adequate ventilation.

6.2 Environmental precautions:

Do not allow to enter sewers / surface or ground water.

6.3 Methods and material for containment and cleaning up:

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 13 for disposal information.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Open and handle receptacle with care.

Do not pierce or burn even after use. Use only as directed on the label.

Do not mix with any other chemical products.

Ensure good ventilation / exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

This product is subject to regulations governing the storage of highly flammable aerosol products.

Storage rooms should be equipped with heat and smoke detectors.

Electrical equipment should be explosion-proof.

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from reducing agents.

Store away from oxidising agents.

Store away from foodstuffs.

Store away from plastic, rubber, aluminum, light-metals.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in vertical position in closed original containers.

Store at temperature from +5°C to +30°C.

Protect from frost.

Store under lock and key and out of the reach of children.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

* SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
CAS: 115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
CAS: 106-97-8 butane, pure	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

DNELs		
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
Oral	DNEL	20 mg/kg/Tag (General population, consumers)
Dermal	DNEL	0.05 mg/kg/Tag (General population, consumers)
Inhalative	DNEL	0.05 mg/m ³ (General population, consumers) 0.05 mg/m ³ (Workers)

PNECs	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(soil)	1 mg/kg

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Short-term contact ≥ 10 min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

EN 166

Body protection: Protective work clothing.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

Different according to colouring

Odour:

Characteristic

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

Not applicable, as aerosol

Lower and upper explosion limit

Lower:

1.5 Vol %

Upper:

11.0 Vol %

Flash point:

<0 °C

Solubility

water:

Insoluble

Reacts with water

Vapour pressure:

>500 kPa (in the container)

< 1*10⁻⁵ mmHg w 25 °C (MDI)

Density and/or relative density

Density at 20 °C:

≤ 1.3 (PMDI) g/cm³

9.2 Other information

Appearance:

Form:

Rapidly curing foam dispensed by gaseous propellant from an aerosol container

Important information on protection of health and environment, and on safety.

Auto-ignition temperature:

> +350 °C (propellant)

Explosive properties:

Heating may cause an explosion

Information with regard to physical hazard classes

Explosives

Void

Flammable gases

Void

Aerosols

Extremely flammable aerosol.

Pressurised container:

May burst if heated

Oxidising gases

Void

Gases under pressure

Void

Flammable liquids

Void

Flammable solids

Void

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Void

Pyrophoric solids

Void

Self-heating substances and mixtures

Void

Substances and mixtures, which emit flammable

gases in contact with water

Void

Oxidising liquids

Void

Oxidising solids

Void

Organic peroxides

Void

Corrosive to metals

Void

Desensitised explosives

Void

SECTION 10: Stability and reactivity

10.1 **Reactivity** No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

- 10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials:**
Strongly reacts with water and other substances containing an active hydrogen atom.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

LD/LC50 values relevant for classification:		
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)
Inhalative	LC50/4h	1.5 mg/l (ATE)
CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate		
Oral	LD50	630-2,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50	>2,000 mg/kg (rat) 7 mg/l (rat)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties		
CAS: 1244733-77-4	tris(2-chlorisopropyl)-phosphate	List II

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

* SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
EC50	1,640 mg/l (algae) >1,000 mg/l (daphnia) (OECD202) >100 mg/l (Sedimentation) (OECD209)
EC50	>1,000 mg/l (fish) (OECD)

12.2 Persistence and degradability Not biodegradable.

12.3 Bioaccumulative potential Does not accumulate in organisms.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:	
CAS: 85535-85-9	chlorinated paraffins, C14-17

vPvB:	
CAS: 85535-85-9	chlorinated paraffins, C14-17

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

* SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of in a safe manner in accordance with local / national regulations.

Do not allow to enter surface or ground water.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

European waste catalogue	
15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising
HP14	Ecotoxic

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022





P PLUS MEGA PISTOL FOAM 65L

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

* SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR, IMDG, IATA	AEROSOLS
14.3 Transport hazard class(es)	
ADR	
	
Class	2.5F Gases.
Label	2.1
IMDG, IATA	
	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	Not applicable.
14.5 Environmental hazards:	
Marine pollutant:	No.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Remarks:	Exemption from ADR provisions by LQ principal (rule 3.4) - Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30 kg. - Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20 kg.
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, UK REACH

1272/2008/CE Regulation, GB CLP

2020/878/UE Regulation

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P3a FLAMMABLE AEROSOLS

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56, 74

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

REGULATION (EC) No 1005/2009 on substances that deplete the ozone layer – ANNEX I (Ozone- depleting potential)

Substances of very high concern (SVHC) according to UK REACH

CAS: 85535-85-9 chlorinated paraffins, C14-17

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Printing date 06.02.2023

Version number 1

Revision: 14.02.2022



P PLUS MEGA PISTOL FOAM 65L

PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Lact.: Reproductive toxicity – effects on or via lactation
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4