

DECLARATION OF PERFORMANCE
Nr. 2024-08-12-1

1. Unique product type identifier:

FOME FLEX 120 SECONDS SPEED TACK ADHESIVE FOAM

2. Tipo, partijos ar serijos numeris ar bet koks kitas elementas, pagal kurį galima identifikuoti statybos produktą:

The batch number is on the packaging.

3. The intended use or uses of the construction product by the manufacturer in accordance with the applicable technical specification:

Polyurethane foam adhesive used for bonding building materials

4. Name of the manufacturer, registered trade name or registered trademark and manufacturer's contact address, factory address:

UAB TEGRA STATE
Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA
Tel.:+37052661167
www.tegrastate.eu
E-mail: info@tegragroup.eu

5. Where applicable, the name and address of the authorised representative with the powers laid down in Article 18(15) of the Law on Construction of the Republic of Lithuania:

Not applicable

6. A system or systems for assessing and verifying the constancy of performance of the construction product as set out in Chapter V of this Regulation:

System 3

7. Name of the certification body or testing laboratory:

Instytut Techniki Budowlanej
ul. Filtrowa 1
00-611 Warszawa

8. Declared performance:

Tensile strength of the anchorage

Base material: silicate

Adhesive material: silicate

Key characteristics		Method
Expansion, mm	<2	EOTA TR 46
Shear strength, kPa	>400	EOTA TR 46
Tensile strength, MPa, joint EPS - adhesive joint 8 mm - ready-mixed concrete a) Under laboratory conditions b) Under laboratory conditions after 6 min c) At 0 C° d) At +30 C°	>0,08	EOTA TR 46
Tensile strength, MPa, joint XPS - adhesive joint 8 mm - concrete ready. a) Under laboratory conditions b) Under laboratory conditions after 6 min c) At 0 C° d) At +30 C°	>0,08	EOTA TR 46
Tensile strength, MPa, for EPS or XPS - adhesive joint 8 mm - bitumen coated concrete. a) under laboratory conditions b) at 0 C°	>0,07	EOTA TR 46
Tensile strength, MPa, joint XPS - adhesive joint 8 mm - underlay At +30 C°, heated to +30 C° on the surface of the underlay (within 24 hours before the test)	>0,08	EOTA TR 46

9. the performance of the product referred to in points 1 and 2 shall be in accordance with the performance declared in point 8.

10. Signed (by and on behalf of the manufacturer): Daniel Počikovskij

Vilnius



(parašas)

2024.08.29

*Eksplatacinių savybių deklaracija parengta pagal „STATYBOS TECHNINĮ REGLAMENTĄ STR 1.01.04:2015“