

Aluminium-coated tape



DESCRIPTION:

Adhesive aluminum coated tape for bonding seams and joints, industrial and domestic. Most often used as a connecting part of reflective thermal coatings (in heating or cooling/refrigeration or plumbing systems). The tape provides long-term protection against corrosion, moisture or vapor permeability. Outstanding property - resistance to high temperatures

APPLICATION:

Manual and automatic carton sealing. Suitable for cold and hot temperatures.

TECHNICAL CHARACTERISTICS:

Carrier type	Metallized BOPP 25 my film
Adhesive type	20 my water-based acrylic
Adhesion on steel [N/25mm]	5.5 +/-1
shear to steel	Over 200 hours
elongation at break MD	150 +/- 30 (%)
tensile strength MD	81 +/- 20 (%)

SIZES:

Width [mm]: 48, 72
 Length [m]: 45
 Core [mm]: 76,2

STORAGE CONDITIONS:

Store in a cool dry place away from sunlight and direct heat sources. As far as the storage conditions are respected, the product is guaranteed 12 months.

DISCLAIMER:

All statements, technical information and product recommendations are based on tests in our laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risks and liability whatsoever in connection therewith. Neither seller or manufacturer shall be reliable for any loss or damage –direct, incidental or consequential – arising of the use of the product.