MASKING TAPE „SUPER GLUE“

Advantages

- Excellent adhesion to most surfaces
- Strong initial adhesion
- For interior protection
- The tape can only remain on for a moderate period of time (7 days)

Areas of application

- For painted walls and trim
- For varnished/lacquered wood
- Glass, plastic, metal
- Masking, bonding, storage, packaging

Composition

Paper	Internally impregnated crepe paper
Glue	Synthetic rubber (hot-melt)

Color

Yellow

Sizes

Width [mm]	19, 25, 30, 38, 48
Length [m]	50

TEGRA
UAB „TEGRA STATE“ Savanoriu ave 178A, LT-03154 Vilnius, LITHUANIA
Tel.:+37052661167, www.tegrastate.eu, info@tegragroup.eu

Physical properties

	STANDARD INDICATORS	MEASUREMENT	TOLERANCE
Thickness	110	my	(+/- 10%)
Adhesion to steel 180°	≥ 8	N/2,5 cm	-
Tensile strength	3,3	kg/cm	(+/- 2%)
Elongation during stretching	9	%	(+/- 2%)
Operating temperature	from –10 to +60	°C	-
	from 14 to 140	F	-

These properties are typical and should not be considered specifications. All properties are approximate and based on reliability testing and pre-approved recommended test methods. These values are provided for comparison purposes only and do not constitute a manufacturer's warranty. Before using the product, the user should determine whether the product is suitable for the intended purpose and is suitable for the user's use.

Storage/transportation conditions

The tape should be stored in its original packaging in a cool, dry place out of direct sunlight and should be used within 12 months of the date of shipment. The surfaces to which the tape is to be applied must be clean, dry and free of grease, oil or other contaminants.