

Polyethylene cover with adhesive reinforced tape for outdoor use



Description

Statically treated and folded HDPE film with UV-resistant PE-coated reinforced fabric masking tape for outdoor use.

Usage

This compact "two-in-one" masking concept can be used for temporary protection indoors and outdoors when painting and plastering. Because of the tape's thick layer of adhesive material, it can be applied to rough, uneven and dusty surfaces. In addition, the tape has excellent UV resistance and controlled adhesion, so it can also be removed after 3 weeks without leaving sticky residues on almost any surface (under moderate sunlight exposure).

Characteristics

Adhesive tape	
Backing	reinforced LDPE
Adhesive	natural rubber
Clean removal	up to 3 weeks from almost all surfaces (under moderate sunlight exposure)
Total thickness [µm]	310
Adhesion to steel RT [N/25mm]	9.5
Tensile strength, MD [N/25 mm]	145
Elongation, MD [%]	10
Film	
Film material	HDPE
Colour	Transparent, milky white
Statically charged	Yes
Thickness [µm]	8

Sizes

Unwound film x roll length:

- 2700 mm x 17 m
- 2100 mm x 17 m
- 1400 mm x 20 m
- 550 mm x 20 m

Storage/transport conditions

Store in a cool, dry place, away from sunlight and direct heat sources. If storage conditions are observed, the product is guaranteed for 12 months.

Additional information

All statements, technical information and product recommendations are based on tests carried out in our laboratories, which we believe to be reliable. However, in all cases the user should determine the product's suitability for the intended use, and the user assumes all related risks and responsibility. Neither the seller nor the manufacturer is liable for any loss or damage, incidental or consequential, arising from the use of the product. Detailed information about the test methods is available upon request.